

Ferotec Friction, Inc

150 Shellyland Road Rapho Business Park
 PO Box 387 Mount Joy, PA 17552
 (717) 492-9600 Fax: (717) 492-9601

Material Safety	D3704	Data Sheet
Telephone: (717) 492-9600 Revision Date: 08/01/2013 Fax: (717) 492-9601		
I. Product Information:		
Product Name: D3704		
Trade Name: Molded Friction Product		
II. NFPA (0 = No Hazard; 4 = Severe Hazard):		
Health = 1	Reactivity = 0	Fire = 1
III. Ingredient Information:		
Hazardous Components	C.A.S. Number	Percent
OSHA PEL (mg/m³)	ACGIH TLV (mg/m³)	
Mineral Wool Fibers	Not Listed	13-24
Synthetic Graphite	7742-42-5	5-12
		5
		5
IV. Physical Data:		
Boiling Point (°F):	NA	Evaporation Rate (Butyl Acetate = 1) NA
Vapor Pressure (mm Hg):	NA	Specific Gravity (Water = 1): 1.77
Water Solubility (%):	Insoluble	Melting Point (°F): NA
Vapor Density (Air = 1):	NA	% Volatile by Volume: NA
Appearance And Odor: Black/Gray with No Odor.		
V. Fire and Explosion Data:		
Flash Point (°F):	Above 600°C	Flammable Limits: LEL = NA UEL = NA
Extinguishing Media:	Water, foam, dry chemical	Unusual Fire and Explosion Hazards: None
Special Fire Fighting Procedures: In a sustained fire, self-contained breathing apparatus (SCBA) should be worn.		
VI. Health Data: A. Summary/Risks:		
Clinical conditions which may be aggravated: Any condition generally aggravated by mechanical irritants in air or on skin.		
Target Organs:	Lungs, skin.	
Acute Health Effects:	Temporary irritation of the mouth, nose, and throat or skin.	
Chronic Health Effects:	Long term effects: lung damage can result when subjected to extended duration of high dust exposure without use of respiratory protection.	
Primary Routes of Entry:	Inhalation	
VI. Health Data: B. Signs/Symptoms of Overexposure:		
Inhalation:	May cause temporary upper respiratory irritation.	
Skin Contact:	Acute - Transient mechanical irritation. Chronic - None.	

Material Safety	D3704	Data Sheet
Ingestion:	Acute - Unlikely to occur. Observe individual, if symptoms develop, consult physician. Chronic - None known.	
Eyes:	Acute - Direct contact will cause mechanical irritation. Chronic - None known.	
VI. Health Data: C. First Aid/Emergency Procedures:		
Inhalation:	Remove from exposure. Get medical help if irritation persists.	
Skin Contact:	Wash with mild soap and running water.	
Ingestion:	Unlikely. Consult physician if unusual reaction is noted.	
Eyes:	Flush with flowing water for at least 15 minutes. If symptoms persist, seek immediate medical attention.	
VII. Reactivity Data:		
Conditions to Avoid: Avoid creating dust. Vacuum when possible.		
Hazardous Decomposition Products: Stable material with no known incompatibilities or inherent hazardous decomposition products, except those named in section III.		
VIII. Spill or Leak Procedures:		
Procedures for Spill/Leak: Use vacuum if dust is involved.		
Waste Management: In accordance with state and local regulations.		
IX. Special Protection Information:		
Goggles:	May be appropriate in certain operations.	
Gloves:	May reduce skin irritation in some operations.	
Respirator:	NIOSH approved nuisance dust respirator if TLV is exceeded.	
Ventilation:	Use local exhaust ventilation.	
Other:	Wear long sleeved shirts, loose fitting clothing and use good personal hygiene.	
Special Consideration for Repair & Maintenance of Contaminated Equipment: None		
X. Special Considerations:		
Special Handling/Storage: Store in a dry place. Label information: "Any fiber or dust may be a hazard to your health. Use respirators and/or dust control measures as well as eye protection when handling or processing this product. Do not ingest."		
Other: Wash with mild soap and warm water after handling. Wash work clothes separately.		
<i>The information and recommendations set forth herein are taken from sources believed to be accurate as of the date thereof; however, Ferotec Friction makes no warranty with respect to the accuracy of the information or the suitability of the recommendations and assumes no liability to any user thereof.</i>		